

2014 CTCC Tire Technical Data

		Super Production Class		China Production Class	
Tire Size		240/610R17 S700	240/610R17 W700	190/570R15 S700	190/570R15 W700
Dimension	Inflation (psi)	26	26	26	26
	Measured Rim	9 J 17	9 J 17	7.0 J 15	7.0 J 15
	S.W.	245	245	203	202
	O.D.	603	607	567	565
	O.C.	1894.8	1907.8	1781.6	1775.4
	Revs/Mile	875	869	931	934
	Permitted Rim	8.5 ~ 9.5	8.5 ~ 9.5	7.0 ~ 8.5	7.0 ~ 8.5
Spring Rate	Inflation (psi) / Load (kgf)	26 / 410	26 / 410	26 / 365	26 / 365
	Rim	9 J 17	9 J 17	7.0 J 15	7.0 J 15
	Vertical (kgf/mm)	30.82	29.72	26.52	26.36
	Lateral (kgf/mm)	36.14	30.72	29.26	24.85
Recommended Inflation Pressure (bar)	Cold (Min.)	1.5	1.5	1.5	1.5
	Hot	2.2 ~ 2.4	2.2 ~ 2.4	2.2 ~ 2.4	2.2 ~ 2.4
Recommended Camber		Max. - 5.0	Max. - 5.0	Max. -5.0	Max. -5.0

* Cold 气压为 常温下的 Pressure